# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** SPL

**Supplier's address:** Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

**Model identifier:** LF023882602

**Type of light source:**

| | | | |
|---|---|---|---|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | E27 | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |

**Product parameters**

| Parameter | Value | Parameter | Value |
|---|---|---|---|
| **General product parameters:** | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 8 | Energy efficiency class | G |
| Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º) | 630 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 500 |
| On-mode power ($P_{on}$), expressed in W | 8,0 | Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 93 |
| Outer dimensions without separate control gear, light- | Height: 135 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image in last page |
| | Width: 95 | | |
| | Depth: 95 | | |

| | | | | |
|---|---|---|---|---|
| ing control parts and non-lighting control parts, if any (millimetre) | | | | |
| Claim of equivalent power[a] | | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordinates (x and y) | 0,463<br>0,400 |
| **Parameters for LED and OLED light sources:** | | | | |
| R9 colour rendering index value | | 57 | Survival factor | 0,96 |
| the lumen maintenance factor | | 0,96 | | |
| **Parameters for LED and OLED mains light sources:** | | | | |
| displacement factor (cos ϕ1) | | 0,90 | Colour consistency in McAdam ellipses | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | | -[b] | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | | 0,1 | Stroboscopic effect metric (SVM) | 0,3 |

[a] '-' : not applicable;

[b] '-' : not applicable;


Spectrum
1.0 = 1.312e+001mW/nm
1.2
1.0
0.8
0.6
0.4
0.2
0.0
380
480
580
680
780
Wavelength (nm)

Model placed on the Union market from 08/10/2021

**EPREL registration number:** 1041951

https://eprel.ec.europa.eu/qr/1041951

**Supplier:** Schiefer Signaal Speciaallampen B.V. (Importer)

**Website:** www.schiefer.nl

**Customer care service:**

**Name:** Schiefer Lighting

**Website:** www.schiefer.nl

**Email:** info@schiefer.nl

**Phone:** +31765037717

**Address:**
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands