

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GreenIce

Supplier's address: Soporte Técnico, Cuenca 31-33, 45940 VALMOJADO TOLEDO, ES

Model identifier: GR-T8SENSIR10W-O-CW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	T8		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers


Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		10	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power (P_{on}), expressed in W		10,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, light-	Height	40	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	30		
	Depth	600		


ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	90	
		Chromaticity coordinates (x and y)	0,392 0,390	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	28	Survival factor	-	
the lumen maintenance factor	-			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,99	Colour consistency in McAdam ellipses	2	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	..(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0	

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 15/11/2021



EPREL registration number: 1075307

<https://eprel.ec.europa.eu/qr/1075307>

Supplier: GREEN ICE S.L. (Importer)

Website: WWW.GREENICE.COM

Customer care service:

Name: Soporte Técnico

Website: www.greenice.com

Email: info@greenice.com

Phone: +34912907521

Address:

Cuenca 31-33
45940 VALMOJADO
Spain