Product Information Sheet


COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources							
Supplier's name or trade mark: Duralamp S.p.A.							
Supplier's address: Customer Care, Via Pratese, 164 50145 Florence - Italy							
Model identifier: LFP45422							
Type of light source:							
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		E14					
(or other electric interface)							
Mains or non-mains:		MLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	Only with spe- cific dimmers			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		340 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200			
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	78	Spectral power dis-	See image			
sions without	Width	45	tribution in the	in last page			
separate con- trol gear, light-		45	range 250 nm to 800 nm, at full-load				

ing control parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power ^(a)		Yes	If yes, equivalent power (W)	31			
			Chromaticity coordi-	0,452			
			nates (x and y)	0,411			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		10	Survival factor	0,90			
the lumen maintenance factor		0,96					
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)		0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,9			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;



Model placed on the Union market from 01/09/2021



EPREL registration number: 1088096 https://eprel.ec.europa.eu/qr/10

88096

Supplier: DURA LAMP SRL (Importer) Website: www.duralamp.com

Customer care service:

Name: Customer Care Website: http://www.duralamp.it

Email: duralamp@duralamp.it Phone: +39055894881

Address:

Via Pratese, 164 50145 Florence - Italy