

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LEDVANCE

**Supplier's address:** LEDVANCE GmbH, Parkring 1-5, 85748 Garching, DE

**Model identifier:** AC41914

## Type of light source:

|                                                     |     |                                 |      |
|-----------------------------------------------------|-----|---------------------------------|------|
| Lighting technology used:                           | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | E27 |                                 |      |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No  | Envelope:                       | -    |
| High luminance light source:                        | No  |                                 |      |
| Anti-glare shield:                                  | No  | Dimmable:                       | Yes  |


## Product parameters

| Parameter                                                                                                                                             | Value                | Parameter                                                                                                                                                  | Value                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                                    |                      |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         | 11                   | Energy efficiency class                                                                                                                                    | G                      |
| Useful luminous flux ( $\Phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 500 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 1 800                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     | 11,0                 | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                    | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without separate control gear, lig-                                                                                                  | Height               | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                       | Width                |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth                |                                                                                                                                                            |                        |


|                                                                                                                         |       |                                       |                |  |
|-------------------------------------------------------------------------------------------------------------------------|-------|---------------------------------------|----------------|--|
| hting control parts and non-lighting control parts, if any (millimetre)                                                 |       |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | Yes   | If yes, equivalent power (W)          | 42             |  |
|                                                                                                                         |       | Chromaticity coordinates (x and y)    | 0,552<br>0,408 |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |       |                                       |                |  |
| R9 colour rendering index value                                                                                         | 0     | Survival factor                       | 0,90           |  |
| the lumen maintenance factor                                                                                            | 0,93  |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |       |                                       |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,70  | Colour consistency in McAdam ellipses | 6              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | ..(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 1,0   | Stroboscopic effect metric (SVM)      | 0,4            |  |

(a) : not applicable;

(b) : not applicable;



Múnla a cuireadh ar mhargadh an Aontais ón méid seo a leanas 10/08/2022.



**Cláruimhir EPREL:** 1212439

<https://eprel.ec.europa.eu/qr/1212439>

**Soláthróir:** LEDVANCE GmbH (Monaróir)

**Suíomh gréasáin:** <http://www.ledvance.com/>

**Seirbhís cúraim custaiméirí:**

**Ainm:** LEDVANCE GmbH

**Suíomh gréasáin:** <http://www.ledvance.com/>

**Seoladh Ríomhphoist:** [contact@ledvance.com](mailto:contact@ledvance.com)

**Guthán:** +49 89-780673-100

**Seoladh:**

Parkring 1-5  
85748 Garching  
Germany