

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** GreenIce

**Supplier's address:** Soporte Técnico, Cuenca 31-33, 45940 VALMOJADO TOLEDO, ES

**Model identifier:** 1916-NS-HVFL200W-FCW

## Type of light source:

|                                                     |       |                                 |                            |
|-----------------------------------------------------|-------|---------------------------------|----------------------------|
| Lighting technology used:                           | LED   | Non-directional or directional: | NDLS                       |
| Light source cap-type (or other electric interface) | Borna |                                 |                            |
| Mains or non-mains:                                 | MLS   | Connected light source (CLS):   | No                         |
| Colour-tuneable light source:                       | No    | Envelope:                       | -                          |
| High luminance light source:                        | No    |                                 |                            |
| Anti-glare shield:                                  | No    | Dimmable:                       | Only with specific dimmers |


## Product parameters

| Parameter                                                                                                                                             | Value                      | Parameter                                                                                                                                                  | Value                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                                    |                            |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         | 200                        | Energy efficiency class                                                                                                                                    | D                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 30 000 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 000                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     | 200,0                      | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                          | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without separate control gear, light-                                                                                                | Height                     | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                       | Width                      |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth                      |                                                                                                                                                            |                        |


|                                                                                                                         |       |                                       |                |  |
|-------------------------------------------------------------------------------------------------------------------------|-------|---------------------------------------|----------------|--|
| ing control parts and non-lighting control parts, if any (millimetre)                                                   |       |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | Yes   | If yes, equivalent power (W)          | 1 070          |  |
|                                                                                                                         |       | Chromaticity coordinates (x and y)    | 0,325<br>0,355 |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |       |                                       |                |  |
| R9 colour rendering index value                                                                                         | 7     | Survival factor                       | -              |  |
| the lumen maintenance factor                                                                                            | -     |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |       |                                       |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,99  | Colour consistency in McAdam ellipses | 2              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | ..(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,9   | Stroboscopic effect metric (SVM)      | 0,9            |  |

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 15/11/2021



**EPREL registration number:** 1945596

<https://eprel.ec.europa.eu/qr/1945596>

**Supplier:** GREEN ICE S.L. (Importer)

**Website:** [WWW.GREENICE.COM](http://WWW.GREENICE.COM)

**Customer care service:**

**Name:** Soporte Técnico

**Website:** [www.greenice.com](http://www.greenice.com)

**Email:** [info@greenice.com](mailto:info@greenice.com)

**Phone:** +34912907521

**Address:**

Cuenca 31-33  
45940 VALMOJADO  
Spain