

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LEDVANCE

**Supplier's address:** LEDVANCE GmbH, Parkring 33, Garching, Germany

**Model identifier:** AC32715

## Type of light source:

|                                                     |       |                                 |     |
|-----------------------------------------------------|-------|---------------------------------|-----|
| Lighting technology used:                           | LED   | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | GU5.3 |                                 |     |
| Mains or non-mains:                                 | NMLS  | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No    | Envelope:                       | -   |
| High luminance light source:                        | No    |                                 |     |
| Anti-glare shield:                                  | No    | Dimmable:                       | No  |

## Product parameters

| Parameter                                                                                                                                             | Value                    | Parameter                                                                                                                                                  | Value                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                                    |                          |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         | 9                        | Energy efficiency class                                                                                                                                    | G                      |
| Useful luminous flux ( $\Phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 621 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     | 8,0                      | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without                                                                                                                              | Height                   | Spectral power distribution in the                                                                                                                         | See image in last page |
|                                                                                                                                                       | Width                    |                                                                                                                                                            |                        |

|                                                                                                   |       |       |                                                                    |                |
|---------------------------------------------------------------------------------------------------|-------|-------|--------------------------------------------------------------------|----------------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Depth | 51    | range 250 nm to 800 nm, at full-load                               |                |
| Claim of equivalent power <sup>(a)</sup>                                                          |       | Yes   | If yes, equivalent power (W)                                       | 50             |
|                                                                                                   |       |       | Chromaticity coordinates (x and y)                                 | 0,455<br>0,405 |
| <b>Parameters for directional light sources:</b>                                                  |       |       |                                                                    |                |
| Peak luminous intensity (cd)                                                                      |       | 1 000 | Beam angle in degrees, or the range of beam angles that can be set | 36             |
| <b>Parameters for LED and OLED light sources:</b>                                                 |       |       |                                                                    |                |
| R9 colour rendering index value                                                                   |       | 1     | Survival factor                                                    | 0,90           |
| the lumen maintenance factor                                                                      |       | 0,70  |                                                                    |                |

(a) : not applicable;

(b) : not applicable;



**EPREL registration number:** 523010

Model placed on the Union market from 14/09/2021 to 04/10/2025.



<https://eprel.ec.europa.eu/qr/523010>

**Supplier:** LEDVANCE GmbH (Manufacturer)

**Website:** <http://www.ledvance.com/>

**Customer care service:**

**Name:** LEDVANCE GmbH

**Website:**

**Email:** [contact@ledvance.com](mailto:contact@ledvance.com)

**Phone:** +49 89-780673-100

**Address:**

Parkring 33, Garching, Germany