Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: LF023870312

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E14		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode power (P_{on}), expressed in W	4,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, light-	Height: 75	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width: 45		
	Depth: 45		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,492 0,410
Parameters for LED and OLED light sources:				
R9 colour rendering index value		61	Survival factor	0,96
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		0,1	Stroboscopic effect metric (SVM)	0,3

[a] '-' : not applicable;

[b] '-' : not applicable;

EVERFINE


SPL Spectrum Test Report

Sample	:	Date	: 2020-04-22 11:36:37
Specification	:	Sam. Status	:
Sample No.	: LF023870312-2	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Schiefer
		Assessor	: damin

Test Condition

Temprature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 53413 (82%)
Test Mode	: Fast Test	T	: 75 ms
		Sensitivity	: High

Spectrum



Spectral Distribution CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: x = 0.4926 y = 0.4103 / u' = 0.2840 v' = 0.5322 (duv=-1.57e-03)

CCT= 2299K Prcp WL: Ld=587.1nm Purity=71.0%

Peak WL: Lp=629nm FWHM: =119.9nm Ratio:R=30.9% G=67.0% B=2.1%

Render Index: Ra = 93.1

R1 =96	R2 =99	R3 =96	R4 =95	R5 =97	R6 =94	R7 =89	
R8 =80	R9 =61	R10=100	R11=98	R12=88	R13=97	R14=99	R15=90

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 246.81 lm Eff. : 64.81 lm/W Fe = 935.40 mW

Electrical parameters

V = 229.9 V I = 0.02108 A P = 3.808 W PF = 0.7857

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 05/03/2021

EPREL registration number: 545628 https://eprel.ec.europa.eu/qr/545628

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer) **Website:** www.schiefer.nl

Customer care service:

Name: Schiefer Lighting **Website:** www.schiefer.nl

Email: info@schiefer.nl **Phone:** +31765037717

Address:
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands