Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L276099927-1

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	E
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	4,2	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control — Height	106	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
Width	60		
Depth	60		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[(a)]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,465 0,419
Parameters for LED and OLED light sources:				
R9 colour rendering index value		10	Survival factor	0,90
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,50	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[(b)]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,4

(a) '-' : not applicable;

(b) '-' : not applicable;

EVERFINE


SPL Spectrum Test Report

Sample	:	Date	: 2021-03-17 11:50:51
Specification	: Sensor A60 4w clear	Sam. Status	:
Sample No.	: Sensor A60 4w clear 01	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Schiefer
		Assessor	: damin


Test Condition

Temprature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 44558 (68%)
Test Mode	: Fast Test	T	: 37 ms
		Sensitivity	: High

Spectrum



Spectral Distribution



CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: x = 0.4647 y = 0.4196 / u' = 0.2616 v' = 0.5315 (duv=2.88e-03)

CCT= 2702K Prcp WL: Ld=583.3nm Purity=65.4%

Peak WL: Lp=607nm FWHM: =116.5nm Ratio:R=25.2% G=72.5% B=2.4%

Render Index: Ra = 83.5

R1 =82	R2 =93	R3 =95	R4 =81	R5 =83	R6 =93	R7 =82	
R8 =59	R9 =10	R10=84	R11=81	R12=77	R13=85	R14=98	R15=74

LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 482.90 lm Eff. : 115.53 lm/W Fe = 1.4942 W

Electrical parameters

V = 229.9 V I = 0.03487 A P = 4.180 W PF = 0.5213

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 23/03/2021

EPREL registration number: 619767 https://eprel.ec.europa.eu/qr/619767

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer) **Website:** www.schiefer.nl

Customer care service:

Name: Schiefer Lighting **Website:** www.schiefer.nl

Email: info@schiefer.nl **Phone:** +31765037717

Address:
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands