

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** OSRAM

**Supplier's address:** LEDVANCE GmbH, Parkring 33, Garching, Germany

**Model identifier:** AC35210

## Type of light source:

|                                                     |         |                                 |      |
|-----------------------------------------------------|---------|---------------------------------|------|
| Lighting technology used:                           | LED     | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | GX24q-4 |                                 |      |
| Mains or non-mains:                                 | MLS     | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No      | Envelope:                       | -    |
| High luminance light source:                        | No      |                                 |      |
| Anti-glare shield:                                  | No      | Dimmable:                       | No   |

## Product parameters

| Parameter                                                                                                                                             | Value                  | Parameter                                                                                                                                                  | Value                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                                    |                        |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         | 20                     | Energy efficiency class                                                                                                                                    | F                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 2 025 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     | 20,0                   | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without separate control gear, lig-                                                                                                  | Height                 | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                       | Width                  |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth                  |                                                                                                                                                            |                        |

|                                                                                                                         |      |                                       |                |  |
|-------------------------------------------------------------------------------------------------------------------------|------|---------------------------------------|----------------|--|
| hting control parts and non-lighting control parts, if any (millimetre)                                                 |      |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -    | If yes, equivalent power (W)          | -              |  |
|                                                                                                                         |      | Chromaticity coordinates (x and y)    | 0,433<br>0,403 |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |                                       |                |  |
| R9 colour rendering index value                                                                                         | 0    | Survival factor                       | 0,90           |  |
| the lumen maintenance factor                                                                                            | 0,70 |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |                                       |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,90 | Colour consistency in McAdam ellipses | 6              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 1,0  | Stroboscopic effect metric (SVM)      | 0,4            |  |


(a) : not applicable;

(b) : not applicable;



Cláruimhir EPREL: 642885

Múnla a cuireadh ar mhargadh an Aontais ón méid seo a leanas 07/09/2021 go dtí 01/06/2024.



<https://eprel.ec.europa.eu/qr/642885>

**Soláthróir:** LEDVANCE GmbH (Monaróir)

**Suíomh gréasáin:** <http://www.ledvance.com/>

**Seirbhís cúraim custaiméirí:**

**Ainm:** LEDVANCE GmbH

**Suíomh gréasáin:**

**Seoladh Ríomhphoist:** [contact@ledvance.com](mailto:contact@ledvance.com)

**Guthán:** +49 89-780673-100

**Seoladh:**

Parkring 33, Garching, Germany