

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SLV

Supplier's address: EPREL-Contact, Daimlerstraße 21-23, 52531 Übach-Palenberg, DE

Model identifier: 1005281

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	GU10		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	13	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 000 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	12,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate con-	Height	Spectral power distribution in the range	See image in last page
	Width		
	Depth		


trol gear, lighting control parts and non-lighting control parts, if any (millimetre)			250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-		If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,380 0,380
Parameters for directional light sources:				
Peak luminous intensity (cd)	13 000		Beam angle in degrees, or the range of beam angles that can be set	10
Parameters for LED and OLED light sources:				
R9 colour rendering index value	76		Survival factor	0,00
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,96		Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	.. ^(b)		If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0		Stroboscopic effect metric (SVM)	0,4

(a) : not applicable;

(b) : not applicable;



Múnla a cuireadh ar mhargadh an Aontais ón méid seo a leanas 01/10/2021



Cláruimhir EPREL: 703362

<https://eprel.ec.europa.eu/qr/703362>

Soláthróir: SLV GmbH (Allmhaireoir)

Suíomh gréasáin: www.slv.com

Seirbhís cúraim custaiméirí:

Ainm: EPREL-Contact

Suíomh gréasáin: www.slv.com

Seoladh Ríomhphoist: eprel@slv.de

Guthán: +49 (0)2451 4833 0

Seoladh:

Daimlerstraße 21-23
52531 Übach-Palenberg
Germany