

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L270016400

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		140 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 000
On-mode power (P_{on}), expressed in W		3,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, light-	Height	145	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	64		
	Depth	64		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,520 0,406	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	12	Survival factor	0,70	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,5	Stroboscopic effect metric (SVM)	0,1	

(a) '-': not applicable;

(b) '-': not applicable;

SPL Spectrum Test Report

Sample :
Specification : L270016400
Sample No. : L270016400 2
Manufacturer : SPL


Date : 2018-09-05 10:53:42
Sam. Status :
Instrument : HaasSuite(EVERFINE)
Test by : Marc
Assessor : damin

Test Condition

Temperature : 25.3Deg
WL Range : 380nm-780nm
Test Mode : Fast Test

RH : 65.0%
IP : 57751 (88%)
T : 115 ms
Sensitivity : High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.5207$ $y = 0.4064$ / $u' = 0.3047$ $v' = 0.5351$ ($duv = -2.31e-03$)

CCT= 2007K Prcp WL: $L_d = 589.6\text{nm}$ Purity=78.3%

Peak WL: $L_p = 615\text{nm}$ FWHM: $\approx 94.8\text{nm}$ Ratio: R=34.0% G=64.1% B=1.8%

Render Index: $R_a = 81.5$

R1 =84 R2 =98 R3 =84 R4 =80 R5 =87 R6 =92 R7 =74

R8 =52 R9 =12 R10=99 R11=84 R12=84 R13=88 R14=92 R15=73

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 143.92 lm Eff. : 41.18 lm/W $F_e = 503.63\text{ mW}$


Electrical parameters

V = 230.0 V I = 0.01610 A P = 3.494 W PF = 0.9438

Schiefer Professional Lighting

www.professional-lighting.eu

Model placed on the Union market from 11/05/2021



EPREL registration number: 765706

<https://eprel.ec.europa.eu/qr/765706>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35

4871EP Etten-Leur

Netherlands