

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: LF023810309

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E14		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200
On-mode power (P_{on}), expressed in W		4,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	95
Outer dimensions without separate control gear, light-	Height	100	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	35		
	Depth	35		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,507 0,410	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	88	Survival factor	0,96	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,3	

(a) '-': not applicable;

(b) '-': not applicable;

SPL Spectrum Test Report

Sample :
 Specification : LF023810309
 Sample No. : LF023810309 - 1
 Manufacturer : SPL


Date : 2018-06-18 13:39:26
 Sam. Status :
 Instrument : HaasSuite(EVERFINE)
 Test by : Marc
 Assessor : damin

Test Condition

Temperature : 25.3Deg
 WL Range : 380nm-780nm
 Test Mode : Fast Test

RH : 65.0%
 IP : 58195 (89%)
 T : 68 ms
 Sensitivity : High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.5071$ $y = 0.4106$ / $u' = 0.2934$ $v' = 0.5346$ ($duv = -1.42e-03$)

CCT= 2155K Prcp WL: Ld=588.0nm Purity=75.5%

Peak WL: Lp=641nm FWHM: =120.3nm Ratio:R=33.1% G=65.0% B=1.9%

Render Index: Ra = 96.3

R1 =98 R2 =97 R3 =99 R4 =98 R5 =97 R6 =93 R7 =95

R8 =94 R9 =88 R10=96 R11=93 R12=87 R13=97 R14=99 R15=98

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 249.49 lm Eff. : 67.23 lm/W Fe = 1.0976 W


Electrical parameters

V = 230.0 V I = 0.02063 A P = 3.711 W PF = 0.7817

Schiefer Professional Lighting

www.professional-lighting.eu

Model placed on the Union market from 31/05/2021



EPREL registration number: 765786

<https://eprel.ec.europa.eu/qr/765786>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35

4871EP Etten-Leur

Netherlands