Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: LF023900105

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 000
On-mode power (P_{on}), expressed in W	6,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, light-	Height: 400	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width: 300		
	Depth: 300		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,548 0,407
Parameters for LED and OLED light sources:				
R9 colour rendering index value		64	Survival factor	0,96
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,85	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		0,1	Stroboscopic effect metric (SVM)	0,3

[a] '-' : not applicable;

[b] '-' : not applicable;

EVERFINE


SPL Spectrum Test Report

Sample	:	Date	: 2021-03-18 09:10:46
Specification	: LF023900105	Sam. Status	:
Sample No.	: LF023900105-1	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Schiefer
		Assessor	: damin


Test Condition

Temprature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 50163 (77%)
Test Mode	: Fast Test	T	: 51 ms
		Sensitivity	: High

Spectrum



Spectral Distribution



CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: x = 0.5483 y = 0.4079 / u' = 0.3226 v' = 0.5400 (duv=1.58e-04)

CCT= 1805K Prcp WL: Ld=590.9nm Purity=87.0%

Peak WL: Lp=641nm FWHM: =112.4nm Ratio:R=38.2% G=60.8% B=1.0%

Render Index: Ra = 93.6

R1 =94	R2 =98	R3 =99	R4 =94	R5 =95	R6 =97	R7 =90	
R8 =81	R9 =64	R10=95	R11=98	R12=94	R13=95	R14=98	R15=89

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 257.58 lm Eff. : 41.46 lm/W Fe = 1.1959 W

Electrical parameters

V = 229.9 V I = 0.03390 A P = 6.213 W PF = 0.7970

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 06/06/2021

EPREL registration number: 768102 https://eprel.ec.europa.eu/qr/768102

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer) **Website:** www.schiefer.nl

Customer care service:

Name: Schiefer Lighting **Website:** www.schiefer.nl

Email: info@schiefer.nl **Phone:** +31765037717

Address:
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands