

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L024070607

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Ba22d		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	540 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	6,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,476 0,413	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	55	Survival factor	0,96	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,3	

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report

Sample : 1
Specification : 0
Sample No. : 61
Manufacturer : SPL


Date : 2016-06-13 09:20:22
Sam. Status :
Instrument : HaasSuite(EVERFINE)
Test by : Schiefer
Assessor : damin

Test Condition

Temperature : 25.3Deg
WL Range : 380nm-780nm
Test Mode : Fast Test

RH : 65.0%
IP : 45201 (69%)
T : 28 ms
Sensitivity : High

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4766$ $y = 0.4131$ / $u' = 0.2722$ $v' = 0.5308$ ($duv = -1.92e-04$)

CCT= 2500K Prcp WL: $L_d = 585.3nm$ Purity=67.1%

Peak WL: $L_p = 626nm$ FWHM: $=135.8nm$ Ratio: R=28.1% G=69.6% B=2.3%

Render Index: $R_a = 91.9$

R1 =92 R2 =98 R3 =98 R4 =91 R5 =92 R6 =97 R7 =89
R8 =78 R9 =55 R10 =94 R11 =92 R12 =87 R13 =94 R14 =100 R15 =87
LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 535.53 lm Eff. : 90.54 lm/W $F_e = 1.9483 W$


Electrical parameters

V = 230.2 V I = 0.03083 A P = 5.915 W PF = 0.8335

EVERFINE CORPORATION

<http://www.everfine.cn>

Model placed on the Union market from 01/09/2021



EPREL registration number: 831218

<https://eprel.ec.europa.eu/qr/831218>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35

4871EP Etten-Leur

Netherlands