Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L024372427-1

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Ba15d		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	2	Energy efficiency class	F
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	190 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	2,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, lighting control — Height	47	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
Outer dimensions without separate control gear, lighting control — Width	17		
Outer dimensions without separate control gear, lighting control — Depth	17		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[(a)]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,464 0,410
Parameters for LED and OLED light sources:				
R9 colour rendering index value		9	Survival factor	0,90
the lumen maintenance factor		0,93		

[(a)] '-' : not applicable;

[(b)] '-' : not applicable;

EVERFINE


SPL Spectrum Test Report

Sample	:	Date	: 2021-03-17 15:15:37
Specification	: L024372427-1	Sam. Status	:
Sample No.	: L024372427-1 01	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Schiefer
		Assessor	: damin

Test Condition

Temprature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 51964 (79%)
Test Mode	: Fast Test	T	: 112 ms
		Sensitivity	: High

Spectrum



Spectral Distribution CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: x = 0.4642 y = 0.4102 / u' = 0.2655 v' = 0.5278 (duv=-4.84e-04)

CCT= 2638K Prcp WL: Ld=584.7nm Purity=62.5%

Peak WL: Lp=608nm FWHM: =109.1nm Ratio:R=25.9% G=71.6% B=2.5%

Render Index: Ra = 82.6

R1 =82	R2 =94	R3 =92	R4 =79	R5 =83	R6 =95	R7 =79	
R8 =56	R9 =9	R10=88	R11=80	R12=79	R13=85	R14=96	R15=74

LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 180.10 lm Eff. : 110.38 lm/W Fe = 559.82 mW

Electrical parameters

V = 12.03 V I = 0.1959 A P = 1.632 W PF = 0.6925

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 01/09/2021

EPREL registration number: 831245 https://eprel.ec.europa.eu/qr/831245

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer) **Website:** www.schiefer.nl

Customer care service:

Name: Schiefer Lighting **Website:** www.schiefer.nl

Email: info@schiefer.nl **Phone:** +31765037717

Address:
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands