

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L226081827

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Ba22d		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	8,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,460 0,411	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	5	Survival factor	0,90	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,75	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a) : not applicable;

(b) : not applicable;


SPL Spectrum Test Report

Sample	:	Date	:	2021-01-04 15:26:01	
Specification	:	Sam. Status	:		
Sample No.	:	L226081827	Instrument	:	HaasSuite(EVERFINE)
Manufacturer	:	Test by	:	Schiefer	
		Assessor	:	damin	

Test Condition

Temperature	:	25.3Deg	RH	:	65.0%
WL Range	:	380nm-780nm	IP	:	50207 (77%)
Test Mode	:	Fast Test	T	:	24 ms
			Sensitivity	:	High

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4603$ $y = 0.4113$ / $u' = 0.2625$ $v' = 0.5277$ ($duv=2.19e-04$)
CCT= 2699K Prcp WL: Ld=584.1nm Purity=61.6%
Peak WL: Lp=605nm FWHM: =112.6nm Ratio:R=25.1% G=72.6% B=2.3%

Render Index: Ra = 82.1

R1 =81 R2 =92 R3 =94 R4 =80 R5 =81 R6 =92 R7 =81
R8 =56 R9 =5 R10=83 R11=80 R12=78 R13=84 R14=97 R15=72
LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters


Flux = 837.34 lm Eff. : 119.88 lm/W Fe = 2.5937 W

Electrical parameters

V = 229.8 V I = 0.04214 A P = 6.985 W PF = 0.7213

Schiefer Professional Lighting
www.spl-lighting.com

Model placed on the Union market from 01/09/2021



EPREL registration number: 831347

<https://eprel.ec.europa.eu/qr/831347>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands