Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L641035927

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	GU10		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	10	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	500 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	10,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	92
Outer dimensions without separate control gear, light-	Height: 73	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width: 110		
	Depth: 110		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,466 0,418
Parameters for directional light sources:				
Peak luminous intensity (cd)		650	Beam angle in degrees, or the range of beam angles that can be set	35
Parameters for LED and OLED light sources:				
R9 colour rendering index value		97	Survival factor	1,00
the lumen maintenance factor		0,75		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,65	Colour consistency in McAdam ellipses	3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		0,1	Stroboscopic effect metric (SVM)	0,3

[a] '-' : not applicable;

[b] '-' : not applicable;

EVERFINE


SPL Spectrum Test Report

Sample	:	Date	: 2021-07-19 13:57:23
Specification	: L641035927	Sam. Status	:
Sample No.	:	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Renee
		Assessor	: damin

Test Condition

Temprature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 51916 (79%)
Test Mode	: Fast Test	T	: 42 ms
		Sensitivity	: High

Spectrum



Spectral Distribution CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: x = 0.4657 y = 0.4184 / u' = 0.2627 v' = 0.5312 (duv=2.38e-03)
CCT= 2680K Prcp WL: Ld=583.6nm Purity=65.4%
Peak WL: Lp=634nm FWHM: =152.1nm Ratio:R=26.9% G=70.9% B=2.2%

Render Index: Ra = 96.3

R1 =98	R2 =97	R3 =94	R4 =98	R5 =97	R6 =96	R7 =98	
R8 =94	R9 =83	R10=91	R11=97	R12=88	R13=97	R14=96	R15=95

LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 511.36 lm Eff. : 99.89 lm/W Fe = 1.9157 W

Electrical parameters

V = 229.8 V I = 0.03354 A P = 5.119 W PF = 0.6641

Schiefer Professional Lighting
www.spl-lighting.com

Model placed on the Union market from 01/09/2021

EPREL registration number: 831545 https://eprel.ec.europa.eu/qr/831545

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer) **Website:** www.schiefer.nl

Customer care service:

Name: Schiefer Lighting **Website:** www.schiefer.nl

Email: info@schiefer.nl **Phone:** +31765037717

Address:
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands