

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L642734827

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	GU10		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	340 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	5,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,463 0,419	
Parameters for directional light sources:				
Peak luminous intensity (cd)	700	Beam angle in degrees, or the range of beam angles that can be set	36	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	3	Survival factor	0,70	
the lumen maintenance factor	0,70			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,70	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,7	Stroboscopic effect metric (SVM)	0,9	

(a) '-': not applicable;

(b) '-': not applicable;

SPL Spectrum Test Report

Sample :
Specification : L642734827
Sample No. : L642734827-298
Manufacturer :


Date : 2021-07-01 11:34:29
Sam. Status :
Instrument : HaasSuite(EVERFINE)
Test by : Renee
Assessor : damin

Test Condition

Temperature : 25.3Deg
WL Range : 380nm-780nm
Test Mode : Fast Test

RH : 65.0%
IP : 47518 (73%)
T : 53 ms
Sensitivity : High

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4636$ $y = 0.4190$ / $u' = 0.2611$ $v' = 0.5311$ ($duv=2.77e-03$)

CCT= 2714K Prcp WL: $L_d=583.3nm$ Purity=64.9%

Peak WL: $L_p=605nm$ FWHM: $=118.4nm$ Ratio:R=24.7% G=73.4% B=2.0%

Render Index: $R_a = 81.6$

$R_1 = 79$ $R_2 = 89$ $R_3 = 97$ $R_4 = 80$ $R_5 = 79$ $R_6 = 88$ $R_7 = 83$

$R_8 = 56$ $R_9 = 3$ $R_{10} = 77$ $R_{11} = 79$ $R_{12} = 73$ $R_{13} = 81$ $R_{14} = 99$ $R_{15} = 71$

LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 366.18 lm Eff. : 73.96 lm/W $F_e = 1.1185 W$


Electrical parameters

V = 229.8 V I = 0.02591 A P = 4.951 W PF = 0.8315

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 01/09/2021 to 24/02/2022



EPREL registration number: 831578

<https://eprel.ec.europa.eu/qr/831578>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35

4871EP Etten-Leur

Netherlands