Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: LF023825302

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	320 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode power (P_{on}), expressed in W	4,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, light-	Height	180	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	125		
	Depth	125		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,478 0,411
Parameters for LED and OLED light sources:				
R9 colour rendering index value		61	Survival factor	0,96
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		0,1	Stroboscopic effect metric (SVM)	0,3

[a] '-' : not applicable;

[b] '-' : not applicable;

EVERFINE


SPL Spectrum Test Report

Sample	:	Date	: 2020-11-04 13:52:19
Specification	: LF023825302	Sam. Status	:
Sample No.	: LF023825302 01	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Schiefer
		Assessor	: damin


Test Condition

Temprature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 53043 (81%)
Test Mode	: Fast Test	T	: 63 ms
		Sensitivity	: High

Spectrum



Spectral Distribution



CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: x = 0.4784 y = 0.4112 / u' = 0.2743 v' = 0.5304 (duv=-9.35e-04)

CCT= 2464K Prcp WL: Ld=585.8nm Purity=67.0%

Peak WL: Lp=626nm FWHM: =129.9nm Ratio:R=28.8% G=69.0% B=2.2%

Render Index: Ra = 93.7

R1 =95	R2 =98	R3 =98	R4 =94	R5 =95	R6 =97	R7 =90	
R8 =81	R9 =61	R10=96	R11=97	R12=89	R13=96	R14=99	R15=89

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 312.88 lm Eff. : 84.02 lm/W Fe = 1.1499 W

Electrical parameters

V = 229.7 V I = 0.02076 A P = 3.724 W PF = 0.7808

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 01/09/2021

EPREL registration number: 831679 https://eprel.ec.europa.eu/qr/831679

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer) **Website:** www.schiefer.nl

Customer care service:

Name: Schiefer Lighting **Website:** www.schiefer.nl

Email: info@schiefer.nl **Phone:** +31765037717

Address:
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands