

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: LF023880688

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode power (P_{on}), expressed in W		5,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, light-	Height	135	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	95		
	Depth	95		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,478 0,415	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	52	Survival factor	0,96	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,3	

(a) '-': not applicable;

(b) '-': not applicable;

SPL Spectrum Test Report

Sample :
Specification : LF023880688
Sample No. : LF023880688 02
Manufacturer : SPL


Date : 2018-04-25 13:01:52
Sam. Status :
Instrument : HaasSuite(EVERFINE)
Test by : Arjan
Assessor : damin

Test Condition

Temperature : 25.3Deg
WL Range : 380nm-780nm
Test Mode : Fast Test

RH : 65.0%
IP : 52069 (79%)
T : 47 ms
Sensitivity : High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4786$ $y = 0.4156$ / $u' = 0.2723$ $v' = 0.5321$ ($duv=6.10e-04$)

CCT= 2496K Prcp WL: $L_d=585.1nm$ Purity=68.4%

Peak WL: $L_p=624nm$ FWHM: $=135.2nm$ Ratio: R=28.0% G=69.7% B=2.3%

Render Index: $R_a = 91.2$

R1 =91 R2 =97 R3 =98 R4 =90 R5 =91 R6 =97 R7 =89

R8 =76 R9 =52 R10=92 R11=90 R12=85 R13=93 R14=100 R15=86

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 402.36 lm Eff. : 72.45 lm/W $F_e = 1.4449 W$


Electrical parameters

V = 230.1 V I = 0.02784 A P = 5.553 W PF = 0.8670

Schiefer Professional Lighting

www.professional-lighting.eu

Model placed on the Union market from 01/09/2021 to 06/06/2023



EPREL registration number: 831797

<https://eprel.ec.europa.eu/qr/831797>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands