Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L270016405

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1 800
On-mode power (P_{on}), expressed in W	3,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, light-	Height: 145 Width: 64 Depth: 64	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,545 0,403
Parameters for LED and OLED light sources:				
R9 colour rendering index value		6	Survival factor	0,70
the lumen maintenance factor		0,93		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		0,5	Stroboscopic effect metric (SVM)	0,1

[a] '-' : not applicable;

[b] '-' : not applicable;

EVERFINE

SPL Spectrum Test Report

Sample	:	Date	: 2018-09-05 11:31:51
Specification	: L270016405	Sam. Status	:
Sample No.	: L270016405 2	Instrument	: HaasSuite(EVERFINE)
Manufacturer	: SPL	Test by	: Marc
		Assessor	: damin

Test Condition

Temprature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 52905 (81%)
Test Mode	: Fast Test	T	: 132 ms
		Sensitivity	: High

Spectrum



Spectral Distribution CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: x = 0.5456 y = 0.4039 / u' = 0.3230 v' = 0.5381 (duv=-1.45e-03)

CCT= 1801K Prcp WL: Ld=591.3nm Purity=85.0%

Peak WL: Lp=620nm FWHM: =93.0nm Ratio:R=37.6% G=61.0% B=1.3%

Render Index: Ra = 79.5

R1 =81	R2 =96	R3 =84	R4 =76	R5 =83	R6 =94	R7 =73	
R8 =48	R9 =6	R10=95	R11=80	R12=87	R13=85	R14=92	R15=70

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 104.50 lm Eff. : 32.68 lm/W Fe = 382.47 mW

Electrical parameters

V = 220.0 V I = 0.01560 A P = 3.198 W PF = 0.9319

Schiefer Professional Lighting
www.professional-lighting.eu

EPREL registration number: 765707 Model placed on the Union market from 11/05/2021 to 31/10/2021.	https://eprel.ec.europa.eu/qr/765707

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer) **Website:** www.schiefer.nl

Customer care service:

Name: Schiefer Lighting **Website:** www.schiefer.nl

Email: info@schiefer.nl **Phone:** +31765037717

Address:
Potterbakkerstraat 35
4871EP Etten-Leur
Netherlands