# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** FIAI

**Supplier's address:** Vertrieb, Egerbach 48, 6334 Schwoich, AT

**Model identifier:** 114683

**Type of light source:**

| | | | |
|---|---|---|---|
| Lighting technology used: | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | WIRE | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | Yes | | |
| Anti-glare shield: | No | Dimmable: | No |

**Product parameters**

| Parameter | Value | Parameter | Value |
|---|---|---|---|
| **General product parameters:** | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 3 | Energy efficiency class | G |
| Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º) | 120 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 |
| On-mode power ($P_{on}$), expressed in W | 2,5 | Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 90 |
| Outer dimensions without separate control gear, lighting control — Height | 54 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image in last page |
| Width | 54 | | |
| Depth | 54 | | |

| | | | | |
|---|---|---|---|---|
| parts and non-lighting control parts, if any (millimetre) | | | | |
| Claim of equivalent power[(a)] | | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordinates (x and y) | 0,381<br>0,382 |
| **Parameters for directional light sources:** | | | | |
| Peak luminous intensity (cd) | | 120 | Beam angle in degrees, or the range of beam angles that can be set | 38 |
| **Parameters for LED and OLED light sources:** | | | | |
| R9 colour rendering index value | | 1 | Survival factor | 0,90 |
| the lumen maintenance factor | | 0,70 | | |

[(a)] '-' : not applicable;

[(b)] '-' : not applicable;


1.2
1.0
0.8
0.6
0.4
0.2
0.0
380
430
480
530
580
630
680
730
780

Model placed on the Union market from 15/06/2020

**EPREL registration number:** 806566

https://eprel.ec.europa.eu/qr/806566

**Supplier:** ISOLED FIAI Handels GmbH (Manufacturer)

**Website:** www.isoled.at

**Customer care service:**

**Name:** Vertrieb

**Website:**

**Email:** office@isoled.at

**Phone:** +43 5372 219999

**Address:**
Egerbach 48, 6334 Schwoich, AT