

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Westal

Supplier's address: Produkt, Fabriksvägen 5, 564 35 Bankeryd, SE

Model identifier: 7504639

Type of light source:

| | | | |
|---|----------------|---------------------------------|------|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | Terminal Block | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | Yes | Dimmable: | No |

Product parameters

| Parameter | Value | Parameter | Value |
|--|------------------------|--|---|
| General product parameters: | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 12 | Energy efficiency class | E |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 450 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P_{on}), expressed in W | 12,0 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,44 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| Outer dimensions without separate control gear, lighting control | Height | 6 | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
| | Width | 230 | |
| | Depth | 230 | |
| | | | See image in last page |


| | | | |
|---|------|------------------------------------|----------------|
| parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,440 0,403 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 4 | Survival factor | 1,00 |
| the lumen maintenance factor | 0,96 | | |

(a) : not applicable;


(b) : not applicable;

Spectrum

1.0 = 3.030e+001mW/nm



Model placed on the Union market from 15/10/2021



EPREL registration number: 1008027

<https://eprel.ec.europa.eu/qr/1008027>

Supplier: Westal AB (Importer)

Website:

Customer care service:

Name: Produkt

Website: <https://www.westal.se/>

Email: timmy.kantola@westal.se

Phone: 0738-26 40 03

Address:

Fabriksvägen 5
564 35 Bankeryd
Sweden