Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			ora with regula to energ	8, 100 cm. 18 cm. 18 mg. 10			
Supplier's name or trade mark: Muuto Supplier's address: Customer Care, Østergade, Copenhagen, DK							
							Model identifier: Top Pendant Ø21
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		GX53					
(or other electric interface)							
Mains or non-mains:		NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	Yes			
		Product para					
Parameter		Value	Parameter	Value			
		General product p					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	G			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		350 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode power (P _{on}), ex- pressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,40			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90			
Outer dimen-	Height	130	Spectral power dis-	See image			
sions without separate con- trol gear, light- ing control	Width Depth	210 210	tribution in the range 250 nm to 800 nm, at full-load	in last page			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,463			
		nates (x and y)	0,411			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	76	Survival factor	-			
the lumen maintenance factor	-					

(a)'-': not applicable; (b)'-': not applicable;

