

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Menu A/S

**Supplier's address:** Riccardo Longo, Aarhusgade 130, 2150 Nordhavn, DK

**Model identifier:** 1680539 Circular Pendant Black

## Type of light source:

|   |           |                                 |      |
|---|-----------|---------------------------------|------|
| Lighting technology used:                           | LED       | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | PCB board |                                 |      |
| Mains or non-mains:                                 | NMLS      | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No        | Envelope:                       | -    |
| High luminance light source:                        | No        |                                 |      |
| Anti-glare shield:                                  | No        | Dimmable:                       | Yes  |

## Product parameters

| Parameter  | Value                   | Parameter  | Value   |
|--|-------------------------|--|---|
| <b>General product parameters:</b>   |                         |  |   |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 12                      | Energy efficiency class  | G   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 863 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700   |
| On-mode power ( $P_{on}$ ), expressed in W   | 12,0                    | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00  |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80  |
| Outer dimensions without separate control gear, lighting control   | Height                  | 350  | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
|  | Width                   | 350  |   |
|  | Depth                   | 8  |   |
|  |                         |  | See image in last page  |

|   |    |                                    |                |  |
|---|----|------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre) |    |                                    |                |  |
| Claim of equivalent power <sup>(a)</sup>                  | -  | If yes, equivalent power (W)       | -              |  |
|   |    | Chromaticity coordinates (x and y) | 0,409<br>0,393 |  |
| <b>Parameters for LED and OLED light sources:</b>         |    |                                    |                |  |
| R9 colour rendering index value                           | 87 | Survival factor                    | -              |  |
| the lumen maintenance factor                              | -  |                                    |                |  |

(a) : not applicable;

(b) : not applicable;

