

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** MS-belysning

**Supplier's address:** AS Metall-Service/MS-Belysning, Gardermovegen 95 B, 2030 NANNESTAD, NO

**Model identifier:** 9400904303

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	integrated LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 800 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power ( $P_{on}$ ), expressed in W	15,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	9	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	1 000	
	Depth	33	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,403
<b>Parameters for directional light sources:</b>			
Peak luminous intensity (cd)	549	Beam angle in degrees, or the range of beam angles that can be set	120
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	1	Survival factor	0,90
the lumen maintenance factor	0,98		


(a) : not applicable;

(b) : not applicable;

# Spectral Curve



Model placed on the Union market from 01/07/2022



**EPREL registration number:** 1285937

<https://eprel.ec.europa.eu/qr/1285937>

**Supplier:** AS METALL-SERVICE (Importer)

**Website:** [www.ms-belysning.no](http://www.ms-belysning.no)

**Customer care service:**

**Name:** AS Metall-Service/MS-Belysning

**Website:** [www.ms-belysning.no](http://www.ms-belysning.no)

**Email:** [post@ms-belysning.no](mailto:post@ms-belysning.no)

**Phone:** +4763888500

**Address:**

Gardermovegen 95 B  
2030 NANNESTAD  
Norway