

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Nordlux

**Supplier's address:** Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

**Model identifier:** 2210449901

## Type of light source:

|   |           |                                 |      |
|---|-----------|---------------------------------|------|
| Lighting technology used:                           | LED       | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | Led strip |                                 |      |
| Mains or non-mains:                                 | MLS       | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No        | Envelope:                       | -    |
| High luminance light source:                        | No        |                                 |      |
| Anti-glare shield:                                  | No        | Dimmable:                       | Yes  |

## Product parameters

| Parameter  | Value               | Parameter  | Value   |
|--|---------------------|--|---|
| <b>General product parameters:</b>   |                     |  |   |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 2                   | Energy efficiency class  | G   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 80 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2200...6500   |
| On-mode power ( $P_{on}$ ), expressed in W   | 1,2                 | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | -   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                   | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80  |
| Outer dimensions without separate control gear, lighting control   | Height              | 500  | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
|  | Width               | 8  |   |
|  | Depth               | 3  |   |
|  |                     |  | See image in last page  |

|   |      |                                       |                |
|---|------|---------------------------------------|----------------|
| parts and non-lighting control parts, if any (millimetre)   |      |                                       |                |
| Claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)          | -              |
|   |      | Chromaticity coordinates (x and y)    | 0,426<br>0,398 |
| <b>Parameters for LED and OLED light sources:</b>   |      |                                       |                |
| R9 colour rendering index value   | 0    | Survival factor                       | 1,00           |
| the lumen maintenance factor  | 0,96 |                                       |                |
| <b>Parameters for LED and OLED mains light sources:</b>   |      |                                       |                |
| displacement factor (cos $\phi_1$ )   | 0,50 | Colour consistency in McAdam ellipses | 6              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)     | -              |
| Flicker metric (Pst LM)   | 1,0  | Stroboscopic effect metric (SVM)      | 0,4            |

(a)-: not applicable;

(b)-: not applicable;

