Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Dyberg Larsen

Supplier's address: Direktionen, Fabriksvej 1, 5466 Middelfart Asperup, DK

Model identifier: 9022

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	NA		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 00 h), rounded st integer	3	Energy efficiency class	G		
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone nrow cone (90º)	230 in Nar- row cone (90°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 100		
On-mode pow pressed in W	ver (P _{on}), ex-	3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
(P _{net}) for CLS, e	andby power expressed in W the second dec-	0,00	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84		
Outer dimen-	Height	138	Spectral power dis-	See image		
sions without	Width	23	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	23	range 250 nm to 800 nm, at full-load	Page 1 /		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	0,429 0,397			
Parameters for directional light sources:						
Peak luminous intensity (cd)	126 299	Beam angle in de- grees, or the range of beam angles that can be set	91			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	12	Survival factor	-			
the lumen maintenance factor	-					

(a)'-' : not applicable;

(b)'-' : not applicable;

