Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or tr	ade mark:	GRAU
-----------------------	-----------	------

Supplier's address: Support, Siemensstrasse 35b, 25462 Rellingen Pinneberg, DE

Model identifier: BR 03 1670 Salt

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Stecker			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Product parameters				
Parameter	Value	Parameter	Value	

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consur mode (kWh/10 up to the neares		5	Energy efficiency class	С	
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	988 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 800	
On-mode pow pressed in W	ver (P _{on}), ex-	5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90	
Outer dimensions without	Height Width	5 102	Spectral power distribution in the	See image in last page	
separate con- trol gear, light- ing control	Depth	102	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,452	
		nates (x and y)	0,408	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	50	Survival factor	1,00	
the lumen maintenance factor	0,98			

(a)'-': not applicable; (b)'-': not applicable;





