

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L277355127

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	320 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	3,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	100	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	55	
	Depth	55	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,471 0,420
Parameters for LED and OLED light sources:			
R9 colour rendering index value	9	Survival factor	0,96
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,75	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,3

(a)-: not applicable;

(b)-: not applicable;


SPL Spectrum Test Report

Sample :	Date :
Specification : L277355127	Sam. Status :
Sample No. : L277355127 02	Instrument : HaasSuite(EVERFINE)
Manufacturer :	Test by : Schiefer
	Assessor : damin

Test Condition

Temperature : 25.3Deg	RH : 65.0%
WL Range : 380nm-780nm	IP : 56709 (87%)
Test Mode : Fast Test	T : 56 ms
	Sensitivity : High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4716$ $y = 0.4119$ / $u' = 0.2695$ $v' = 0.5296$ ($duv = -3.48e-04$)

CCT= 2554K Prcp WL: Ld=585.1nm Purity=65.2%

Peak WL: Lp=608nm FWHM: =109.9nm Ratio:R=26.5% G=71.5% B=2.0%

Render Index: Ra = 82.7

R1 =82 R2 =92 R3 =94 R4 =81 R5 =82 R6 =93 R7 =81
R8 =57 R9 =9 R10=84 R11=81 R12=80 R13=84 R14=98 R15=73

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 385.44 lm Eff. : 115.58 lm/W Fe = 1.2158 W


Electrical parameters

V = 230.0 V I = 0.02881 A P = 3.335 W PF = 0.5033

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 02/03/2021



EPREL registration number: 543792

<https://eprel.ec.europa.eu/qr/543792>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35

4871EP Etten-Leur

Netherlands