

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** OSRAM

**Supplier's address:** LEDVANCE GmbH, Parkring 33, Garching, Germany

**Model identifier:** AC34046

## Type of light source:

|   |           |                                 |      |
|---|-----------|---------------------------------|------|
| Lighting technology used:                           | LFL_T5_HO | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | G5        |                                 |      |
| Mains or non-mains:                                 | NMLS      | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No        | Envelope:                       | -    |
| High luminance light source:                        | No        |                                 |      |
| Anti-glare shield:                                  | No        | Dimmable:                       | Yes  |


## Product parameters

| Parameter  | Value                  | Parameter  | Value   |
|--|------------------------|--|---|
| <b>General product parameters:</b>   |                        |  |   |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 24                     | Energy efficiency class  | G   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 570 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500   |
| On-mode power ( $P_{on}$ ), expressed in W   | 22,4                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00  |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 90  |
| Outer dimensions without separate control gear, lighting control   | Height                 | 563  | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
|  | Width                  | 16   |   |
|  | Depth                  | 16   |   |
|  |                        |  | See image in last page  |


|   |   |                                    |                |
|---|---|------------------------------------|----------------|
| parts and non-lighting control parts, if any (millimetre) |   |                                    |                |
| Claim of equivalent power <sup>(a)</sup>                  | - | If yes, equivalent power (W)       | -              |
|   |   | Chromaticity coordinates (x and y) | 0,313<br>0,327 |

(a): not applicable;

(b): not applicable;



Model placed on the Union market from 03/09/2021



**EPREL registration number:** 546282

<https://eprel.ec.europa.eu/qr/546282>

**Supplier:** LEDVANCE GmbH (Manufacturer)

**Website:** <http://www.ledvance.com/>

**Customer care service:**

**Name:** LEDVANCE GmbH

**Website:**

**Email:** [contact@ledvance.com](mailto:contact@ledvance.com)

**Phone:** +49 89-780673-100

**Address:**

Parkring 33, Garching, Germany