

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: NOWODVORSKI

Supplier's address: NOWODWORSKI SPÓŁKA JAWNA, Bojemskiego 11, 42-202 Częstochowa, PL

Model identifier: 8760

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	25	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 100
On-mode power (P_{on}), expressed in W	23,6	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	196	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	73	
	Depth	215	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,434 0,412
Parameters for directional light sources:			
Peak luminous intensity (cd)	11 972	Beam angle in degrees, or the range of beam angles that can be set	21
Parameters for LED and OLED light sources:			
R9 colour rendering index value	65	Survival factor	-
the lumen maintenance factor	-		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,70	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,0

(a) '-': not applicable;

(b) '-': not applicable;

Spectral distribution



Model placed on the Union market from 01/09/2021



EPREL registration number: 642682

<https://eprel.ec.europa.eu/qr/642682>

Supplier: NOWODWORSKI SPÓŁKA JAWNA (Manufacturer)

Website:

Customer care service:

Name: NOWODWORSKI SPÓŁKA JAWNA

Website:

Email: p.kotnowska@nowodvorski.com

Phone: +48 34 344 91 10

Address:

Bojemskiego 11
42-202 Częstochowa
Poland