

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: LF023825809

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	550 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200
On-mode power (P_{on}), expressed in W	8,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions	Height	Spectral power distribution in the	See image in last page
	Width		
			125

without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Depth	125	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,510 0,412
Parameters for LED and OLED light sources:				
R9 colour rendering index value		93	Survival factor	0,96
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)		0,85	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		0,1	Stroboscopic effect metric (SVM)	0,3

(a)-: not applicable;

(b)-: not applicable;


SPL Spectrum Test Report

Sample	: 1-1	Date	: 2018-01-23 11:05:38
Specification	:	Sam. Status	:
Sample No.	: LF023825809-2	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Ralf
		Assessor	: damin

Test Condition

Temperature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 45154 (69%)
Test Mode	: Fast Test	T	: 22 ms
		Sensitivity	: High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.5107$ $y = 0.4126$ / $u' = 0.2948$ $v' = 0.5359$ ($duv = -7.33e-04$)

CCT= 2134K Prcp WL: $L_d = 588.0nm$ Purity=77.1%

Peak WL: $L_p = 644nm$ FWHM: $= 117.5nm$ Ratio: R=33.4% G=64.7% B=1.9%

Render Index: $R_a = 96.5$

R1 =97 R2 =97 R3 =99 R4 =96 R5 =96 R6 =93 R7 =97

R8 =96 R9 =93 R10=95 R11=92 R12=87 R13=96 R14=98 R15=99

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 567.37 lm Eff. : 78.79 lm/W $F_e = 2.5396 W$

Electrical parameters

V = 230.1 V I = 0.03895 A P = 7.201 W PF = 0.8037

Schiefer Professional Lighting

www.professional-lighting.eu