

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L641215927

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	GU10		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	650 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	12,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	92
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,457 0,409	
Parameters for directional light sources:				
Peak luminous intensity (cd)	2 400	Beam angle in degrees, or the range of beam angles that can be set	15	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	51	Survival factor	1,00	
the lumen maintenance factor	0,75			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	3	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,3	

(a) '-': not applicable;


(b) '-': not applicable;

SPL Spectrum Test Report

Sample	:	Date	:	2021-07-23 08:44:27
Specification	:	Sam. Status	:	
Sample No.	:	Instrument	:	HaasSuite(EVERFINE)
Manufacturer	:	Test by	:	Renee
		Assessor	:	damin

Test Condition

Temperature	:	25.3Deg	RH	:	65.0%
WL Range	:	380nm-780nm	IP	:	45692 (70%)
Test Mode	:	Fast Test	T	:	22 ms
			Sensitivity	:	High

Spectrum**Colorimetric Parameters**

Chromaticity Coordinate: $x = 0.4567$ $y = 0.4082$ / $u' = 0.2615$ $v' = 0.5260$ ($duv = -6.28e-04$)

CCT = 2726K Prcp WL: Ld=584.3nm Purity=59.6%

Peak WL: Lp=618nm FWHM: =117.4nm Ratio:R=26.8% G=70.6% B=2.6%

Render Index: Ra = 93.0

R1 = 96 R2 = 99 R3 = 96 R4 = 96 R5 = 97 R6 = 94 R7 = 88
 R8 = 77 R9 = 51 R10 = 99 R11 = 98 R12 = 86 R13 = 98 R14 = 99 R15 = 88
 LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 843.87 lm Eff. : 105.83 lm/W Fe = 2.8223 W


Electrical parameters

V = 229.9 V I = 0.03566 A P = 7.974 W PF = 0.9726

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 29/04/2021



EPREL registration number: 710905

<https://eprel.ec.europa.eu/qr/710905>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35

4871EP Etten-Leur

Netherlands