

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ECO LIGHT

**Supplier's address:** ECO LIGHT Sp. z o.o., ul. Działkowa 2A 62-872 Borek k. Kalisza, PL

**Model identifier:** EC79449

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E14		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	630 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power ( $P_{on}$ ), expressed in W	7,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, lighting control	Height	100	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	37	
	Depth	37	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,380 0,380
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	7	Survival factor	1,00
the lumen maintenance factor	0,96		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,50	Colour consistency in McAdam ellipses	3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1

(a)-: not applicable;

(b)-: not applicable;

Light Source Test Report



**Color Parameters:**

Chromaticity Coordinate:  $x=0.3817$   $y=0.3843$   
 Chromaticity Coordinate:  $u'=0.3817$   $v'=0.3843$  (duv=3.13e-03)  
 Tc=4021K Dominant WL:Ld=577.4nm Purity=29.9% Centroid WL:569.0nm  
 Ratio:R=19.4% G=77.5% B=3.1% Peak WL:Lp=595.0nm HWL:152.9nm  
 Render Index:Ra=82.5  
 R1 =80 R2 =87 R3 =94 R4 =83 R5 =81 R6 =83 R7 =87  
 R8 =65 R9 =7 R10=70 R11=82 R12=65 R13=82 R14=97 R15=74

**Photo Parameters:**

Flux: 634.27 lm Efficacy:90.87 lm/W

**Electrical Parameters:**

Luminaire: U=230.4V I=0.04960A P=6.98W PF=0.5764

**Instrument Status:**


Scan Range:380.0nm-800.0nm Interval:5.0nm[0] Ip=26377(G=6,D=79)  
 REF=16968(R=4) %=-1.425% PMT: 25.4 centigrade [25.1]

---

Product Type:C37  
 Number:0000000216  
 Temperature:25.3 deg  
 Test Operator:SD  
 Software:V2.00.100

Manufacturer:EVERFINE  
 Test Department:SDZM  
 Humidity:65.0%  
 Test Date:2021-08-02 14:23:02  
 Instrument:PMS-50SSA\_V1 (SN:11040019)

Model placed on the Union market from 01/09/2021



**EPREL registration number:** 761159

<https://eprel.ec.europa.eu/qr/761159>

**Supplier:** ECO LIGHT SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ (Importer)

**Website:** [www.ecolight.pl](http://www.ecolight.pl)

**Customer care service:**

**Name:** ECO LIGHT Sp. z o.o.

**Website:**

**Email:** [marcin.wos@ecolight.pl](mailto:marcin.wos@ecolight.pl)

**Phone:** 505991688

**Address:**

ul. Działkowa 2A 62-872 Borek k. Kalisza  
Poland