
Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: FIAI						
Supplier's address: Vertrieb, Egerbach 48, 6334 Schwoich, AT						
Model identifier: 112340						
Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type		GU5.3				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		Yes				
Anti-glare shield:		No	Dimmable:	No		
Product parameters						
Parameter		Value General product p	Parameter	Value		
Energy consumption in on-		6	Energy efficiency	F		
mode (kWh/1000 h), rounded up to the nearest integer		U	class	'		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		600 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W		6,4	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85		
Outer dimen-	Height	50	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	50 56	tribution in the range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,383 0,379		
Parameters for directional light sources:					
Peak luminous intensity (cd)	600	Beam angle in degrees, or the range of beam angles that can be set	120		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	1	Survival factor	0,90		
the lumen maintenance factor	0,70				

(a)'-': not applicable; (b)'-': not applicable;



Model placed on the Union market from 07/07/2014



EPREL registration number: 805692 https://eprel.ec.europa.eu/qr/805692

Supplier: FIAI Handels GmbH (Manufacturer) Website: www.isoled.at

Customer care service:

Name: Vertrieb Website:

Email: office@isoled.at Phone: +43 5372 219999

Address:

Egerbach 48, 6334 Schwoich, AT