Product Information Sheet


COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: FIAI						
Supplier's address: Vertrieb, Egerbach 48, 6334 Schwoich, AT						
Model identifier: 114249						
Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type		WIRE				
(or other electri	c interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		Yes				
Anti-glare shield:		No	Dimmable:	Only with spe- cific dimmers		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		16	Energy efficiency class	С		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 550 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W		16,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	93		
Outer dimen-	Height	1	Spectral power dis-	See image		
sions without	Width	10	tribution in the	in last page		
separate con- trol gear, light-	Depth	1	range 250 nm to 800 nm, at full-load			

ing control parts and non-lighting control parts, if any (millimetre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,382			
		nates (x and y)	0,384			
Parameters for directional light sources:						
Peak luminous intensity (cd)	2 550	Beam angle in degrees, or the range of beam angles that can be set	120			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	63	Survival factor	0,90			
the lumen maintenance factor	0,70					

(a)_{'-'}: not applicable;

(b)_{'-'} : not applicable;



Model placed on the Union market from 05/06/2019



EPREL registration number: 806791 https://eprel.ec.europa.eu/qr/806791

Supplier: FIAI Handels GmbH (Manufacturer) Website: www.isoled.at

Customer care service:

Name: Vertrieb Website: https://isoled.shop

Email: office@isoled.at Phone: +43 5372 219999

Address: Egerbach 48 6334 Schwoich

Austria