

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Sales, Potterbakkerstraat 35, 4871EP Etten-Leur Noord Brabant, NL

Model identifier: L151800830

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Ba15d		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	D
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	840 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	6,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions	Height	Spectral power distribution in the	See image in last page
	Width		
			18

without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Depth	18	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,442
Parameters for LED and OLED light sources:				
R9 colour rendering index value	10	Survival factor		0,90
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses		6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)		-
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)		0,1

(a)-: not applicable;

(b)-: not applicable;


SPL Spectrum Test Report

Sample	:	Date	: 2021-03-17 16:00:18
Specification	: L151800830	Sam. Status	:
Sample No.	: L151800830 02	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Schiefer
		Assessor	: damin

Test Condition

Temperature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 49866 (76%)
Test Mode	: Fast Test	T	: 25 ms
		Sensitivity	: High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4417$ $y = 0.4039$ / $u' = 0.2538$ $v' = 0.5220$ ($duv = -7.05e-04$)

CCT= 2919K Prcp WL: Ld=583.4nm Purity=53.8%

Peak WL: Lp=606nm FWHM: =125.3nm Ratio:R=23.7% G=73.9% B=2.4%

Render Index: Ra = 83.4

R1 =82 R2 =92 R3 =96 R4 =82 R5 =82 R6 =90 R7 =83

R8 =60 R9 =10 R10=81 R11=82 R12=73 R13=85 R14=99 R15=75

LEVEL:OUT WHITE:ANSI_3000K

Photometric & Radiometric Parameters

Flux = 844.29 lm Eff. : 140.32 lm/W Fe = 2.5829 W

Electrical parameters

V = 229.9 V I = 0.02946 A P = 6.017 W PF = 0.8883

Schiefer Professional Lighting

www.spl-lighting.com