

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L270013005

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	50 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1 800
On-mode power (P_{on}), expressed in W	2,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, light-	Height	185	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	30	
	Depth	30	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,536 0,410
Parameters for LED and OLED light sources:			
R9 colour rendering index value	6	Survival factor	0,70
the lumen maintenance factor	0,93		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,5	Stroboscopic effect metric (SVM)	0,1

(a): not applicable;

(b): not applicable;


SPL Spectrum Test Report

Sample	:	Date	: 2021-04-22 14:59:31
Specification	: L270013005	Sam. Status	:
Sample No.	: L270013005 01	Instrument	: HaasSuite(EVERFINE)
Manufacturer	:	Test by	: Schiefer
		Assessor	: damin

Test Condition

Temperature	: 25.3Deg	RH	: 65.0%
WL Range	: 380nm-780nm	IP	: 50525 (77%)
Test Mode	: Fast Test	T	: 198 ms
		Sensitivity	: High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.5361$ $y = 0.4105$ / $u' = 0.3129$ $v' = 0.5391$ ($duv = -2.91e-04$)

CCT= 1909K Prcp WL: $L_d = 589.8\text{nm}$ Purity=84.2%

Peak WL: $L_p = 618\text{nm}$ FWHM: =102.6nm Ratio:R=34.9% G=63.7% B=1.3%

Render Index: $R_a = 79.4$

R1 =79 R2 =94 R3 =88 R4 =74 R5 =79 R6 =96 R7 =75

R8 =50 R9 =6 R10=89 R11=75 R12=89 R13=82 R14=94 R15=69

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 75.620 lm Eff. : 32.52 lm/W Fe = 273.45 mW

Electrical parameters

V = 230.0 V I = 0.01106 A P = 2.326 W PF = 0.9140

Schiefer Professional Lighting

www.spl-lighting.com