

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: LF023825709

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200
On-mode power (P_{on}), expressed in W	6,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, light-	Height	180	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	125	
	Depth	125	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,514 0,409
Parameters for LED and OLED light sources:			
R9 colour rendering index value	83	Survival factor	0,96
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,3

(a): not applicable;

(b): not applicable;


SPL Spectrum Test Report

Sample :	Date : 2020-02-25 14:52:02
Specification : LF023825709	Sam. Status :
Sample No. : LF023825709 01	Instrument : HaasSuite(EVERFINE)
Manufacturer :	Test by : Schiefer
	Assessor : damin

Test Condition

Temperature : 25.3Deg	RH : 65.0%
WL Range : 380nm-780nm	IP : 51727 (79%)
Test Mode : Fast Test	T : 31 ms
	Sensitivity : High

Spectrum



Spectral Distribution

CIE1931 Chromaticity Diagram

Colorimetric Parameters

Chromaticity Coordinate: $x = 0.5148$ $y = 0.4095$ / $u' = 0.2991$ $v' = 0.5354$ ($duv = -1.57e-03$)

CCT= 2077K Prcp WL: Ld=588.7nm Purity=77.4%

Peak WL: Lp=639nm FWHM: =111.3nm Ratio:R=34.4% G=63.8% B=1.7%

Render Index: Ra = 95.6

R1 =98 R2 =97 R3 =99 R4 =97 R5 =97 R6 =92 R7 =94

R8 =91 R9 =83 R10=96 R11=91 R12=86 R13=97 R14=98 R15=97

LEVEL:OUT WHITE:OUT

Photometric & Radiometric Parameters

Flux = 490.80 lm Eff. : 81.21 lm/W Fe = 2.1106 W

Electrical parameters

V = 229.9 V I = 0.03423 A P = 6.044 W PF = 0.7680

Schiefer Professional Lighting

www.spl-lighting.com