

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Elobra

Supplier's address: Kundensupport, ELOBRA GmbH & Co. KG Zum Hohen Schacht 1a 09618 Brand-Erbisdorf
Geschäftsführer: Dipl. Ing. Peter Lohse

Model identifier: 4019698139349

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	SMD LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	Yes	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:


Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	300 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	3,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85
Outer dimensions without separate control gear, light-	Height	200	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	200	
	Depth	250	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,100 0,100
Parameters for directional light sources:			
Peak luminous intensity (cd)	300	Beam angle in degrees, or the range of beam angles that can be set	120
Parameters for LED and OLED light sources:			
R9 colour rendering index value	80	Survival factor	1,00
the lumen maintenance factor	1,00		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	1,00	Colour consistency in McAdam ellipses	1
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	.. ^(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a)'.': not applicable;

(b)'.': not applicable;

Model placed on the Union market from 31/12/2016



EPREL registration number: 839172

<https://eprel.ec.europa.eu/qr/839172>

Supplier: Elobra GmbH & Co. KG (Manufacturer)

Website:

Customer care service:

Name: Kundensupport

Website: www.elobra.de

Email: shop@elobr.de

Phone: +4935142667643

Address:

ELOBRA GmbH & Co. KG

Zum Hohen Schacht 1a

09618 Brand-Erbisdorf

Geschäftsführer: Dipl. Ing. Peter Lohse