

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: &Tradition

Supplier's address: &Tradition, Kronprinsesse gade 4, 1306 Copenhagen Denmark, DK

Model identifier: Copenhagen SC13 LED

Type of light source:

| | | | |
|---|-----|---------------------------------|----------------------------|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | N/A | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |

Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|


General product parameters:

| | | | |
|--|-------------------------|--|---|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 8 | Energy efficiency class | G |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 610 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2200...2900 |
| On-mode power (P_{on}), expressed in W | 7,5 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 92 |
| Outer dimensions without separate control gear, light- | Height | 2 | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
| | Width | 52 | |
| | Depth | 52 | |
| | | | See image in last page |


| | | | |
|---|------|---------------------------------------|----------------|
| ing control parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,437 0,396 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 56 | Survival factor | 0,96 |
| the lumen maintenance factor | 0,95 | | |
| Parameters for LED and OLED mains light sources: | | | |
| displacement factor (cos ϕ_1) | 0,99 | Colour consistency in McAdam ellipses | 3 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | 0,0 | Stroboscopic effect metric (SVM) | 0,0 |

(a): not applicable;

(b): not applicable;



Model placed on the Union market from 01/09/2021



EPREL registration number: 852245

<https://eprel.ec.europa.eu/qr/852245>

Supplier: &Tradition A/S (Manufacturer)

Website:

Customer care service:

Name: &Tradition

Website: <https://www.andtradition.com/>

Email: info@andtradition.com

Phone: +45 3920 0233

Address:

Kronprinsesse gade 4
1306 Copenhagen
Denmark