

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Deko-Light

**Supplier's address:** Product Management, Deko-Light Elektronik Vertriebs GmbH, Auf der Hub 2, D-76307 Karlsbad, DE

**Model identifier:** 565258

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	other electrical		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers


## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	31	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 400 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power ( $P_{on}$ ), expressed in W	30,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate con-	Height	33	Spectral power distribution in the See image in last page
	Width	77	
	Depth	394	


trol gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-		If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,434 0,403
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	4 709		Beam angle in degrees, or the range of beam angles that can be set	44
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	54		Survival factor	0,90
the lumen maintenance factor	0,70			

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 05/04/2017



**EPREL registration number:** 861603

<https://eprel.ec.europa.eu/qr/861603>

**Supplier:** Deko-Light Elektronik-Vertriebs GmbH (Manufacturer)

**Website:** <https://deko-light.com/>

**Customer care service:**

**Name:** Product Management, Deko-Light Elektronik Vertriebs GmbH

**Website:** <https://deko-light.com/>

**Email:** [pm@deko-light.com](mailto:pm@deko-light.com)

**Phone:** +4972489271724

**Address:**

Auf der Hub 2  
D-76307 Karlsbad  
Germany