

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ANTIDARK

Supplier's address: Antidark Aps, damgårdvej 2, 5500 Middelfart , DK

Model identifier: 2-215-27-1

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	Yes


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	818 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1800...3000
On-mode power (P_{on}), expressed in W	11,8	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	80	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	120	
	Depth	120	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,439 0,405
Parameters for directional light sources:			
Peak luminous intensity (cd)	1 873	Beam angle in degrees, or the range of beam angles that can be set	113
Parameters for LED and OLED light sources:			
R9 colour rendering index value	68	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	1,00	Colour consistency in McAdam ellipses	3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a) : not applicable;

(b) : not applicable;



Color Parameters:

Chromaticity Coordinate: $x=0.4398$ $y=0.4052$ $u'=0.2519$ $v'=0.5223$

$T_c=2962K$ (Duv=0.0001) Dominant WL:Ld =583.0nm Purity=53.6%

Red Ratio:R=26.0% Peak WL:Lp=626.9nm HWL:Lhd=163.3nm

Render Index:Ra=91.7

R1 =93	R2 =94	R3 =92	R4 =92	R5 =91	R6 =90	R7 =95	
R8 =87	R9 =68	R10=82	R11=91	R12=71	R13=93	R14=94	R15=91

Photo Parameters:

Flux = 776.8 lm Eff. : 65.52 lm/W Fe = 2.764 W

Electrical parameters:

V = 33.88 V I = 0.3499 A P = 11.86 W PF = 1.000

LEVEL:OUT WHITE:ANSI_3000K

Status: Integral T = 56 ms Ip = 53493 (82%)

Model:	Number:2-215-27-1
Tester:Rioon	Date:2021-11-13
Temperature:25.3Deg	Humidity:65.0%
Manufactory:ANTIDARK	Remarks: