

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ANTIDARK

Supplier's address: Antidark Aps, damgårdvej 2, 5500 Middelfart , DK

Model identifier: 2-512-06-1

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	Yes


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 323 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	14,4	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	80	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	260	
	Depth	260	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,500 0,500
Parameters for directional light sources:			
Peak luminous intensity (cd)	431	Beam angle in degrees, or the range of beam angles that can be set	120
Parameters for LED and OLED light sources:			
R9 colour rendering index value	90	Survival factor	1,00
the lumen maintenance factor	1,00		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	1,00	Colour consistency in McAdam ellipses	3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a) '-': not applicable;

(b) '-': not applicable;



Color Parameters:

Chromaticity Coordinate: $x=0.4618$ $y=0.4141$ $u'=0.2622$ $v'=0.5290$

$T_c=2700K$ ($Duv=0.0011$) Dominant WL:Ld =583.8nm Purity=62.9%

Red Ratio:R=28.1% Peak WL:Lp=624.0nm HWL:Lhd=144.0nm

Render Index:Ra=92.8

R1 =93 R2 =96 R3 =99 R4 =93 R5 =93 R6 =96 R7 =92

R8 =81 R9 =58 R10=90 R11=95 R12=83 R13=94 R14=98 R15=88

Photo Parameters:

Flux = 1189 lm Eff. : 83.38 lm/W Fe = 4.196 W

Electrical parameters:

V = 28.52 V I = 0.4999 A P = 14.26 W PF = 1.000

LEVEL:OUT WHITE:ANSI_2700K

Status: Integral T = 32 ms Ip = 51271 (78%)