

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** asalite

**Supplier's address:** Monoki Péter, Vak Bottyán 22/a, 4033 Debrecen Hajdú-Bihar, HU

**Model identifier:** ASAL0156

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	G9		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	360 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power ( $P_{on}$ ), expressed in W	3,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	50	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	16	
	Depth	1	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	32
		Chromaticity coordinates (x and y)	0,441 0,402
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	6	Survival factor	0,90
the lumen maintenance factor	0,95		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,00	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)-: not applicable;

(b)-: not applicable;

**Light Source Test Report**



**Color Parameters:**

Chromaticity Coordinate:  $x=0.4413$   $y=0.4028$   
 Chromaticity Coordinate:  $u'=0.4413$   $v'=0.4028$  ( $duv=-1.06e-03$ )  
 Tc=2918K Dominant WL:Ld=583.5nm Purity=53.4% Centroid WL:593.0nm  
 Ratio:R=25.3% G=72.4% B=2.3% Peak WL:Lp=605.0nm HWL:121.1nm  
 Render Index:Ra=82.1  
 R1 =81 R2 =92 R3 =95 R4 =79 R5 =81 R6 =90 R7 =81  
 R8 =57 R9 =6 R10=81 R11=79 R12=72 R13=83 R14=98 R15=73

**Photo Parameters:**

Flux: 382.08 lm Fe: 1.1975 W Efficacy:106.8 lm/W

**Electrical Parameters:**


Luminaire: U=231.1V I=0.03404A P=3.576W PF=0.4545

*Instrument Status:*

Scan Range:380.0nm-800.0nm Interval:5.0nm[0]  $I_p=209$  (G=2,D=49)  
 REF=16086 (R=4)  $\%=-3.141\%$  PMT: 23.8 centigrade [33.3]

Product Type:0156 G9 3W 3000K 3720C Manufacturer:  
 Number:2070 Test Department:  
 Temperature:25.3 deg Humidity:65.0%  
 Test Operator:H Test Date:2020-11-04 16:07:51  
 Software:V2.00.100 Instrument:PMS-50SSA\_V1 (SN:11040002)

Model placed on the Union market from 06/11/2019



**EPREL registration number:** 948707

<https://eprel.ec.europa.eu/qr/948707>

**Supplier:** Asalite Lighting Kft. (Importer)

**Website:** [www.asalite.com](http://www.asalite.com)

**Customer care service:**

**Name:** Monoki Péter

**Website:** [www.asalite.com](http://www.asalite.com)

**Email:** [petermonoki@asalite.com](mailto:petermonoki@asalite.com)

**Phone:** +36704333200

**Address:**

Vak Bottyán 22/a

4033 Debrecen

Hungary