

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LIGHT-POINT

Supplier's address: ceo, GRØNNEGADE 3, 2 SAL , 1107 KØBENHAVN K KØBENHAVN K, DK

Model identifier: 270521 ANGLE+

Type of light source:

| | | | |
|---|------------|---------------------------------|----------------------------|
| Lighting technology used: | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | LED Module | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |

Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

General product parameters:

| | | | |
|--|--------------------------|--|---|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 9 | Energy efficiency class | E |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 726 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 |
| On-mode power (P_{on}), expressed in W | 6,0 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 90 |
| Outer dimensions without separate control gear, light- | Height | 136 | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
| | Width | 121 | |
| | Depth | 85 | |
| | | | See image in last page |

| | | | |
|---|-----|--|----------------|
| ing control parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,434 0,403 |
| Parameters for directional light sources: | | | |
| Peak luminous intensity (cd) | 130 | Beam angle in degrees, or the range of beam angles that can be set | 40 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 55 | Survival factor | - |
| the lumen maintenance factor | - | | |

(a) '-': not applicable;

(b) '-': not applicable;

